

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1 (currently amended) A printing material web processing machine, comprising:

at least one press cylinder for printing a web;

a dryer disposed downstream of said press cylinder, said dryer
~~guiding the web along a path;~~

a pull roll disposed downstream of said dryer for conveying the web along said path with a given tensile stress that is considerably lower than a tensile stress in a printing path upstream of said at least one press cylinder;

a first apparatus disposed downstream of said press cylinder and upstream of said dryer for separating the web from said press cylinder during a normal printing operation, said separating of the web from said press cylinder being decoupled from the conveying of said web along said path; and

a second apparatus for driving said pull roll, said second apparatus driving said pull roll at a rotational speed being

Applic. No. 10/781,113
Response Dated June 26, 2006
Responsive to Office Action of February 24, 2006

reduced as compared with a rotational speed of said press cylinder.

Claim 2 (original) The printing material web processing machine according to claim 1, wherein said second apparatus for driving said pull roll has a third apparatus for controlling the rotational speed of said pull roll and of said press cylinder, said third apparatus controls the rotational speed of said pull roll to a value below a value of the rotational speed of said press cylinder.

Claim 3 (original) The printing material web processing machine according to claim 1, wherein said first apparatus for separating the web from said press cylinder separates the web from said press cylinder without contact.

Claim 4 (original) The printing material web processing machine according to claim 3, wherein said first apparatus has at least one element selected from the group consisting of blowing elements and ultrasound elements.

Claim 5 (original) The printing material web processing machine according to claim 1, wherein the printing material web processing machine is a web-fed rotary offset press.

Applic. No. 10/781,113

Response Dated June 26, 2006

Responsive to Office Action of February 24, 2006

Claim 6 (original) The printing material web processing machine according to claim 1, wherein said first apparatus for separating the web from said press cylinder is configured or coated in an ink-repellent manner, at least in some sections.

Claim 7 (currently amended) A printing material web processing machine, comprising:

at least one press cylinder for printing a web;

a dryer disposed downstream of said press cylinder, said dryer
guiding the web along a path;

~~the separation of the web from said press cylinder being
decoupled from the conveying of said web along said path;~~

a first pull roll disposed downstream of said dryer to convey the web along the path with a given tensile stress which is considerably lower than a tensile stress in a printing path upstream of said at least one press cylinder;

a second pull roll, which is disposed downstream of said press cylinder and upstream of said dryer, and releases for releasing the web during a normal printing operation; and

Applic. No. 10/781,113

Response Dated June 26, 2006

Responsive to Office Action of February 24, 2006

an apparatus for driving said first pull roll, said apparatus driving said first pull roll at a rotational speed being reduced as compared with a rotational speed of said second pull roll.

Claim 8 (original) The printing material web processing machine according to claim 7, wherein said apparatus for driving said first pull roll has a further apparatus for controlling the rotational speeds of said first and said second pull roll, said further apparatus controls the rotational speed of said first pull roll to a value below a value of the rotational speed of said second pull roll.

Claim 9. (original) The printing material web processing machine according to claim 7, wherein said second pull roll is configured or coated in an ink-repellent manner, at least in some sections.

Claim 10 (original) The printing material web processing machine according to claim 7, wherein said first pull roll is a cooling roll.

Claim 11 (original) The printing material web processing machine according to claim 7, wherein said first and second

Applic. No. 10/781,113
Response Dated June 26, 2006
Responsive to Office Action of February 24, 2006

pull rolls are in each case constructed as a driven, rotating element.

Claim 12 (original) The printing material web processing machine according to claim 7, wherein said first pull roll and said press cylinder are in each case constructed as a driven, rotating element.

Claim 13 (original) The printing material web processing machine according to claim 7, wherein the printing material web processing machine is a web-fed rotary offset press.

Claim 14 (currently amended) A method for treating a printing material web in a printing material web processing machine, which further comprises:

feeding a web to a press cylinder under a first tensile stress;

printing on the web using the press cylinder;

conveying the web along a drying path;

separating the web from the press cylinder during a normal printing operation, the separating of the web from the press

Applic. No. 10/781,113

Response Dated June 26, 2006

Responsive to Office Action of February 24, 2006

cylinder being decoupled from the conveying of the web along the path; and

setting a second tensile stress of the web, being considerably reduced as compared with the first tensile stress, along the drying path.

Claim 15 (original) The method according to claim 14, which further comprises setting the second tensile stress to a value suitable for conveying the web after separation from the press cylinder.

Claim 16 (original) The method according to claim 14, which further comprises conveying the web along the drying path composed of path parts which follow one another and are oppositely curved.

Claim 17 (original) The method according to claim 14, which further comprises controlling the second tensile stress such that the drying path is composed of path parts which follow one another and are oppositely curved.

Claim 18 (original) The method according to claim 14, which further comprises controlling the second tensile stress such that the drying path is substantially meander-like.

Applic. No. 10/781,113

Response Dated June 26, 2006

Responsive to Office Action of February 24, 2006

Claim 19 (original) The method according to claim 14, which further comprises controlling the second tensile stress to a value less than 50 N/m.

Claim 20 (original) The method according to claim 14, which further comprises controlling the second tensile stress such that the drying path has a radii of curvature following one another of in each case less than 200 mm.

Claim 21 (original) The method according to claim 14, which further comprises increasing a temperature of the web along the drying path.

Claim 22 (original) The method according to claim 14, which further comprises controlling the second tensile stress such that the drying path is substantially sinusoidal.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.